

Item		Buyer Model	LP-H808FA0	
		LG Model	LP-H808FA0	
General	Cooling Capacity		kcal/hr(W)	22786(26500)
			Btu/hr	90000
	Heating Capacity		kcal/hr(W)	24080(28000)
			Btu/hr	95000
	Input	Cooling/Heating	W	10000/10000
	Running Current	Cooling/Heating	A	19/19
	Starting Current	Cooling/Heating	A	47.5/47.5
	Power Supply		Ø,V,Hz	3,380-415,50
	Power Factor		%	89
	E.E.R	Cooling	kcal/hr W(W/W)	-
			Btu/hr W	-
	C.O.P	Heating	kcal/hr W(W/W)	-
			Btu/hr W	-
	Setting temperature range(cool/heat)		°C	18~30/16~30
	Dehumidification Rate		l/h	10
Refrigerant Control			Capillary Tube	
Refrigerant Charge		g(oz), type	7,500(264),R22	
Indoor	Indoor fan motor	Output	w	389
		Model		-
		No. of Poles		6
		Input	W	570
		Running Current	A	3.4
		Capacitor	µF/Vac	40/400
	Indoor Fan	Type		SIRROCO
		No. Used / Diameter	EA/mm(inch)	1/7.5(190)
	Indoor Fan RPM	Cooling(H/M/L)	rpm	760/ - /690
		Heating(H/M/L)	rpm	760/ - /690
	Air Circulation	Indoor (H/M/L)	CFM	60/ - /55(2117/ - /1946)
	Noise Level(Sound Press)	Indoor(H/M/L)	dB(A)+3	60/ - /58
	Temperature Controller			Thermistor
	Indoor Coil	Tube Size (OD)	inch(mm)	3/8(9.52)
		Fins per inch		17
No. of Rows & Column		3R 31C		
Dimensions (W*H*D)	Indoor	mm	41.4*74*19.5(1050*1880*495)	
Net Weight	indoor	kg(lbs)	120(264)	
Compressor	Locked Rotor Amp.	A	65.8	
	Type		Scroll	
	Quantity	No	2	
	Model		JT160BATY1L	
	Maker		DAIKIN	
	Capacity	kcal/hr(Btu/hr)	12905(51200)	
	Motor Type		PSC	
	Motor Input	W	4660	
	Oil Type		SUNISO 4GSDID-K	
	Oil Charge	cc	1400	
	O.L.P Type(model name)		(INTERIOR)	

Outdoor	Outdoor Coil	Tube Size (OD)	mm	0.28(7)
		Fins per inch		18
		No. of Rows & Column		1R*17C/2R*17C/2R*36C
	Outdoor fan motor	Output	w	271
		Model		A8UW566FA0
		No. of Poles		6
		Input	W	429
		Running Current	A	1.87
	Outdoor Fan	Capacitor	μF/Vac	10/370
		Type		PRPELLER
		No. Used / Diameter	EA/mm	2/20.71(526)
		Discharge	Top / Side	Top Discharge
	Air Circulation	Speed	rpm	850
Outdoor		CMM(CFM)	-	
Noise Level(Sound Press,1m)	Outdoor	dB(A)+3	64	
SVC Valve	Liquid	inch(mm)	9/8(28)	
	Gas	inch(mm)	1/2(12.7)	
Dimensions (W*H*D)	Outdoor	mm	0.43*61.47*27.19(1280*1560*690)	
Net Weight	Outdoor	kg	250(528)	
Other	Power supply Cable		No.* mm2	5*5.5
	Conncting Cable		No.* mm2	6*1.5
	Connecting Tube Socket Flare) (Ø)	Liquid Side	inch(mm)	1/2(12.7)
		Gas Side	inch(mm)	9/8(28)
		Length, std	m	7.5
		Max length/elevation	m	50/30
	Drain hose (ID Ø)	Indoor Unit	mm	25
		Outdoor Unit	mm	-
	Packing Dimension (W*H*D)	Indoor Unit	mm	44.3*75.7*22.4(1124*1920*568)
				52.4*61.9*29.2(1330*1570*740)
Stuffing Quantity	With (Without) S/Par	20/40ft	7/16(7/16)	